

1. Description

The Everlux adhesive is a Silicone Elastomer product with an easy and clean fixing and which dries quickly. It shows a high resistance to pulling off and to humidity and allows it to be glued to irregular surfaces. This adhesive has excellent mechanical properties, high grip in various materials, and high elasticity; it is resistant to temperature variation and to UV rays.

This glue was especially developed for the best fixing of the Everlux signs without requiring screws or nails. Tests show that it provides the best adherence to most surfaces where signs are fixed.

2. Characteristics

- Aspect: Pasty.
- Colour: White.
- Smell: Acetic acid
- Viscosity: High fluidity that allows easy application (extrusion).
- Density: 0.97 g/cm³
- Time to form a film: 10 minutes
- Minimum Temperature of application: +5° C
- Resistance to temperature: -40 °C a +100 °C
- Temperature range for application: +5 °C a +40°C

3. Directions to use

- The temperature for fixing must be between +5 °C and +40 °C.
- The signs and the surfaces where they are going to be applied must be dry and with no dust, mud, oil or grease.
- Apply the Everlux adhesive using a manual or pneumatic pistol.
- Apply a 5mm continuous string of the adhesive at approximately 1cm of the edge in the rear face of the sign.
- Complete the process by pressing on the sign against the wall/surface in order to squeeze and to get an even distribution of the adhesive.
- Each tube is provided with a cover for the tip in order to prevent drying of the adhesive.

4. Packaging and spread

Cartridge of 300 ml.

Considering a line of 5mm diameter, approximately 15 metres long, which means:

Sign size (mm)	Quantity of signs	Sign size (mm)	Quantity of signs	Sign size (mm)	Quantity of signs	Sign size (mm)	Quantity of signs
150x150	29	200x200	21	200x300	17	400x300	12
150x200	25	300x150	19	400x200	14	600x400	8

5. Storage and time it lasts

Store between +5 °C and +25 °C in a dry and fresh place.

To be used within 18 months after the manufacturing date shown in the tube.

After this period, the adhesive keeps all of its properties if the tube is kept sealed and stored under the indicated conditions.

6. Hygiene and Safety

Apply the product in well-ventilated areas. In case of contact of the product not cured with skin or eyes, wash the affected area with water and seek medical advice.

For further information, please consult the relative Safety Data Sheet.